



EDITION AUGUST 2026
AUSTRALIA

COPPER FITTINGS FOR HVACR

Product Catalogue

Brazing-type copper fittings for air conditioning and refrigeration, in three pressure-rated ranges. Manufactured to AS/NZS 1200, AS/NZS 1571 and AS/NZS 5149, under ISO 9001 quality systems.

Vantage 45

45 BAR · PREFIX AC

Ascent 70

UP TO 70 BAR · PREFIX RC

Summit 130

130 BAR · PREFIX CO

Vantage 45 AC 45 bar 4.5 MPa nominal rating Size range 1/4"–4-1/8" · DN8–DN100 Material Copper C12200 (99.9%) Refrigerants R-32, R-410A, low-GWP	Ascent 70 RC Up to 70 bar 7 MPa for smaller sizes Size range 1/4"–4-1/8" · DN8–DN100 Material Copper C12200 (99.9%) Refrigerants R-134a, R-404A, R-32, R-410A, R-448A	Summit 130 CO 130 bar 13 MPa / 1885 psi at 150°C Size range 3/8"–2-1/8", 2-5/8" · DN10–DN67 Material Copper-iron alloy CuFe2P Refrigerants R-744 (CO₂)
--	---	---

Operating temperature: Vantage 45 -10°C to 65°C · Ascent 70 -25°C to 65°C · Summit 130 -196°C to 150°C

HOW TO READ A PART NUMBER																											
AC 7LT- 18																											
AC	7LT-	18																									
Range prefix	Fitting stem, shown in each table heading	Size in sixteenths of an inch (1-1/8" = 18)																									
Build the part number from the range prefix, the stem in the table heading, and the size code beside the size.																											
<table><tr><td>3/16" 03</td><td>1/4" 04</td><td>5/16" 05</td><td>3/8" 06</td></tr><tr><td>1/2" 08</td><td>5/8" 10</td><td>3/4" 12</td><td>7/8" 14</td></tr><tr><td>1" 16</td><td>1-1/8" 18</td><td>1-1/4" 20</td><td>1-3/8" 22</td></tr><tr><td>1-1/2" 24</td><td>1-5/8" 26</td><td>2" 32</td><td>2-1/8" 34</td></tr><tr><td>2-1/2" 40</td><td>2-5/8" 42</td><td>3" 48</td><td>3-1/8" 50</td></tr><tr><td>3-5/8" 58</td><td>4-1/8" 66</td><td>6-1/8" 98</td><td></td></tr></table>				3/16" 03	1/4" 04	5/16" 05	3/8" 06	1/2" 08	5/8" 10	3/4" 12	7/8" 14	1" 16	1-1/8" 18	1-1/4" 20	1-3/8" 22	1-1/2" 24	1-5/8" 26	2" 32	2-1/8" 34	2-1/2" 40	2-5/8" 42	3" 48	3-1/8" 50	3-5/8" 58	4-1/8" 66	6-1/8" 98	
3/16" 03	1/4" 04	5/16" 05	3/8" 06																								
1/2" 08	5/8" 10	3/4" 12	7/8" 14																								
1" 16	1-1/8" 18	1-1/4" 20	1-3/8" 22																								
1-1/2" 24	1-5/8" 26	2" 32	2-1/8" 34																								
2-1/2" 40	2-5/8" 42	3" 48	3-1/8" 50																								
3-5/8" 58	4-1/8" 66	6-1/8" 98																									
Reading the tables. A dot means the size is stocked in that range. Reducing fittings are listed largest end first. All fittings are brazing type; flare and compression are not suitable. Stated pressures are indicative; the stated temperature is the reference point for the rating, not a ceiling on gas temperature.																											

Manufacturing and quality

- Manufactured to AS/NZS 1200, AS/NZS 1571 and AS/NZS 5149.
- Ascent 70 and Summit 130 also meet AS 4041; Summit 130 is designed to UL 207.
- Made under ISO 9001 quality systems, and pressure tested to AS/NZS 5149 before commissioning.
- Summit 130 burst pressure is indicatively above 390 bar, more than 3x design.

Installation guidelines

- Braze oxygen-free with a nitrogen purge to prevent internal oxidation.
- Minimum 5% silver alloy on Ascent 70; minimum 15% on Summit 130.
- Ensure fully brazed joints, then pressure test to AS/NZS 5149 before startup. Verify Summit 130 design pressures for transcritical operation.
- Design pipework to avoid mechanical and thermal stress.
- Burst testing is performed after brazing to replicate field conditions. Due to variables such as vibration, temperature, pressure and pulsation, end-users should verify suitability for their specific application.

45° Elbow F x F 6-

SIZE · CODE	45	70	130
1/4" 04	•	•	
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1" 16	•		
1-1/8" 18	•	•	•
1-3/8" 22	•	•	•
1-5/8" 26	•	•	•
2-1/8" 34	•	•	•
2-5/8" 42		•	
3-1/8" 50		•	

45° Elbow M x F 6-2-

SIZE · CODE	45	70	130
1/4" 04		•	
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1-1/8" 18	•	•	•
1-3/8" 22	•	•	•
1-5/8" 26		•	•
2-1/8" 34	•	•	•
2-5/8" 42		•	

90° Long Radius Elbow F x F 7LT-

SIZE · CODE	45	70	130
1/4" 04	•	•	
5/16" 05	•	•	
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1" 16	•		
1-1/8" 18	•	•	•
1-1/4" 20	•		
1-3/8" 22	•	•	•
1-5/8" 26	•	•	•
2-1/8" 34	•	•	•
2-5/8" 42	•	•	•
3-1/8" 50		•	
3-5/8" 58		•	
4-1/8" 66		•	

90° Long Radius Elbow M x F 7LT-2-

SIZE · CODE	45	70	130
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1-1/8" 18	•	•	•
1-3/8" 22	•	•	•
1-5/8" 26	•	•	•
2-1/8" 34	•	•	•
2-5/8" 42	•	•	•
3-1/8" 50		•	
3-5/8" 58		•	
4-1/8" 66		•	

90° Long Radius Elbow M x M 7LT-2-2-

SIZE · CODE	45	70	130
5/8" 10		•	
1-3/8" 22		•	
1-5/8" 26		•	
2-1/8" 34		•	

90° Long Radius Reducing Elbow F x F 7LT-

SIZE · CODE	45	70	130
5/8 × 1/2 10-08		•	
7/8 × 5/8 14-10		•	
7/8 × 3/4 14-12		•	
1-1/8 × 7/8 18-14		•	
1-3/8 × 1-1/8 22-18		•	
1-5/8 × 1-3/8 26-22		•	
2-1/8 × 1-5/8 34-26		•	

90° Short Radius Elbow F x F 7-

SIZE · CODE	45	70	130
1/4" 04	•	•	
3/8" 06	•	•	
1/2" 08	•	•	
5/8" 10	•	•	
3/4" 12	•	•	
7/8" 14	•	•	
1-1/8" 18	•	•	
1-3/8" 22	•	•	
1-5/8" 26	•	•	
2-1/8" 34	•	•	
2-5/8" 42		•	
3-1/8" 50	•	•	
3-5/8" 58		•	
4-1/8" 66	•	•	
6-1/8" 98		•	

90° Short Radius Elbow M x F 7-2-

SIZE · CODE	45	70	130
1/4" 04	•	•	
3/8" 06	•	•	
1/2" 08	•	•	
5/8" 10	•	•	
3/4" 12	•	•	
7/8" 14	•	•	
1-1/8" 18	•	•	
1-3/8" 22	•	•	
1-5/8" 26	•	•	
2-1/8" 34	•	•	
2-5/8" 42		•	
4-1/8" 66	•		

90° Short Radius Reducing Elbow F x F 7-

SIZE · CODE	45	70	130
3/8 × 1/4 06-04		•	
5/8 × 1/2 10-08		•	
7/8 × 5/8 14-10		•	

Reducing Bushing M x F 02-

SIZE · CODE	45	70	130
3/8 × 1/4 06-04	•	•	
1/2 × 1/4 08-04	•	•	
1/2 × 3/8 08-06	•	•	•
5/8 × 3/8 10-06	•	•	•
5/8 × 1/2 10-08	•	•	•
3/4 × 3/8 12-06	•		•
3/4 × 1/2 12-08		•	•
3/4 × 5/8 12-10	•	•	•
7/8 × 3/8 14-06		•	•
7/8 × 1/2 14-08		•	•
7/8 × 5/8 14-10	•	•	•
7/8 × 3/4 14-12	•	•	•
1-1/8 × 1/2 18-08	•	•	•
1-1/8 × 5/8 18-10	•	•	•
1-1/8 × 3/4 18-12	•	•	•
1-1/8 × 7/8 18-14	•	•	•
1-3/8 × 5/8 22-10		•	•
1-3/8 × 7/8 22-14		•	•
1-3/8 × 1-1/8 22-18	•	•	•
1-5/8 × 5/8 26-10		•	
1-5/8 × 7/8 26-14	•	•	•
1-5/8 × 1-1/8 26-18	•	•	•
1-5/8 × 1-3/8 26-22		•	•
2-1/8 × 5/8 34-10		•	
2-1/8 × 7/8 34-14		•	•
2-1/8 × 1-1/8 34-18		•	•
2-1/8 × 1-3/8 34-22	•	•	•
2-1/8 × 1-5/8 34-26	•	•	•
2-5/8 × 1-1/8 42-18		•	
2-5/8 × 1-3/8 42-22		•	
2-5/8 × 1-5/8 42-26		•	
2-5/8 × 2-1/8 42-34			•
2-5/8 × 2-1/8 42-44		•	

Reducing Bushing M x F (cont.) 02-

SIZE · CODE	45	70	130
3-1/8 × 1-3/8 50-22		•	
3-1/8 × 2-1/8 50-34	•	•	
3-1/8 × 2-5/8 50-42		•	
3-5/8 × 2-1/8 58-34		•	
3-5/8 × 3-1/8 58-50		•	
4-1/8 × 2-5/8 66-42		•	
4-1/8 × 3-1/8 66-50	•	•	

Cap 17-

SIZE · CODE	45	70	130
1/4" 04		•	
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1-1/8" 18	•	•	•
1-3/8" 22	•	•	•
1-5/8" 26	•	•	•
2-1/8" 34	•	•	•
2-5/8" 42		•	•
3-1/8" 50		•	
4-1/8" 66	•	•	

Reducing Coupling 0-

SIZE · CODE	45	70	130
3/8 × 1/4 06-04	•	•	
3/8 × 5/16 06-05	•	•	
1/2 × 1/4 08-04	•	•	
1/2 × 3/8 08-06	•	•	•
5/8 × 1/4 10-04		•	
5/8 × 3/8 10-06	•	•	
5/8 × 1/2 10-08	•	•	•
3/4 × 3/8 12-06		•	
3/4 × 1/2 12-08	•	•	
3/4 × 5/8 12-10	•	•	•
7/8 × 3/8 14-06		•	
7/8 × 1/2 14-08		•	
7/8 × 5/8 14-10	•	•	
7/8 × 3/4 14-12	•	•	•
1-1/8 × 1/2 18-08		•	•
1-1/8 × 5/8 18-10	•	•	
1-1/8 × 3/4 18-12	•	•	
1-1/8 × 7/8 18-14	•	•	•
1-1/8 × 1 18-16	•		
1-3/8 × 1/2 22-08			•
1-3/8 × 5/8 22-10	•	•	•
1-3/8 × 3/4 22-12			•
1-3/8 × 7/8 22-14	•	•	•
1-3/8 × 1-1/8 22-18	•	•	•
1-5/8 × 5/8 26-10	•	•	
1-5/8 × 3/4 26-12			•
1-5/8 × 7/8 26-14	•	•	•
1-5/8 × 1-1/8 26-18	•	•	•

Reducing Coupling (cont.) 0-

SIZE · CODE	45	70	130
1-5/8 × 1-3/8 26-22	•	•	•
2-1/8 × 5/8 34-10		•	
2-1/8 × 7/8 34-14		•	
2-1/8 × 1-1/8 34-18	•	•	
2-1/8 × 1-3/8 34-22		•	•
2-1/8 × 1-5/8 34-26	•	•	•
2-5/8 × 1-1/8 42-18		•	
2-5/8 × 1-3/8 42-22		•	
2-5/8 × 1-5/8 42-26	•	•	
2-5/8 × 2-1/8 42-34	•	•	
3-1/8 × 1-5/8 50-26		•	
3-1/8 × 2-1/8 50-34		•	
3-1/8 × 2-5/8 50-42		•	
4-1/8 × 3-1/8 66-34		•	
4-1/8 × 2-5/8 66-42		•	

Coupling w/roll stop 0-

SIZE · CODE	45	70	130
1/4" 04	•	•	
3/8" 06	•	•	
1/2" 08	•	•	
5/8" 10	•	•	
3/4" 12	•	•	
7/8" 14	•	•	
1" 16	•		
1-1/8" 18	•	•	
1-3/8" 22	•	•	
1-5/8" 26	•	•	
2-1/8" 34	•	•	•
2-5/8" 42		•	•
3-1/8" 50		•	
3-5/8" 58		•	
4-1/8" 66	•	•	

Coupling w/stake stop 0-5-

SIZE · CODE	45	70	130
5/16" 05	•	•	
3/8" 06	•		•
1/2" 08	•		•
5/8" 10	•		•
3/4" 12	•		•
7/8" 14	•		•
1" 16	•		
1-1/8" 18	•		•
1-3/8" 22			•
1-5/8" 26	•		•
2-1/8" 34	•		

Coupling, no stop 0-NSTOP-

SIZE · CODE	45	70	130
1/4" 04		•	
3/8" 06		•	
1/2" 08		•	
5/8" 10		•	
3/4" 12		•	
7/8" 14		•	
1-1/8" 18		•	
1-3/8" 22		•	

Female Adapter C x F 3-

SIZE · CODE	45	70	130
1/4 × 1/8 04-02		•	
1/4 × 1/4 04-04		•	
1/4 × 3/8 04-06		•	
3/8 × 1/4 06-04		•	
3/8 × 3/8 06-06		•	
1/2 × 3/8 08-06	•	•	
1/2 × 1/2 08-08	•	•	
5/8 × 1/4 10-04	•	•	
5/8 × 3/8 10-06	•	•	
5/8 × 1/2 10-08	•	•	
5/8 × 3/4 10-12	•	•	
3/4 × 1/2 12-08		•	
3/4 × 3/4 12-12		•	
7/8 × 1/2 14-08	•	•	
7/8 × 3/4 14-12	•	•	
7/8 × 1 14-16		•	
1-1/8 × 1/2 18-08	•		
1-1/8 × 3/4 18-12	•		
1-1/8 × 1 18-16		•	•
1-3/8 × 1-1/4 22-20	•	•	
1-5/8 × 1-1/2 26-24	•	•	
2-1/8 × 2 34-32	•	•	
2-5/8 × 2-1/2 42-40		•	

Female Adapter FTG x F 3-2-

SIZE · CODE	45	70	130
5/8 × 3/8 10-06	•		
5/8 × 1/2 10-08	•		
1-1/8 × 1 18-16	•		
2-1/8 × 2 34-32	•		

Male Adapter C x M 4-

SIZE · CODE	45	70	130
1/4 × 1/4 04-04		•	
1/4 × 3/8 04-06		•	
3/8 × 1/8 06-02	•		
3/8 × 1/4 06-04		•	
3/8 × 3/8 06-06		•	
3/8 × 1/2 06-08		•	
1/2 × 3/8 08-06	•	•	
1/2 × 1/2 08-08		•	
1/2 × 3/4 08-12		•	
5/8 × 3/8 10-06	•	•	
5/8 × 1/2 10-08	•	•	

Male Adapter C x M (cont.) 4-

SIZE · CODE	45	70	130
5/8 × 3/4 10-12	•	•	
3/4 × 1/2 12-08		•	
3/4 × 3/4 12-12		•	
7/8 × 1/2 14-08		•	
7/8 × 3/4 14-12	•	•	
7/8 × 1 14-16	•	•	
1-1/8 × 3/4 18-12	•	•	
1-1/8 × 1 18-16	•	•	
1-3/8 × 1 22-16	•	•	
1-3/8 × 1-1/4 22-20	•	•	
1-3/8 × 1-1/2 22-24		•	
1-5/8 × 1-1/4 26-20		•	
1-5/8 × 1-1/2 26-24	•	•	
2-1/8 × 1-1/2 34-24		•	
2-1/8 × 2 34-32	•	•	
2-5/8 × 2 42-32		•	
2-5/8 × 2-1/2 42-40		•	
3-1/8 × 3 50-48		•	

Male Adapter FTG x M 4-2-

SIZE · CODE	45	70	130
7/8 × 3/4 14-12	•		
1-1/8 × 1 18-16	•		

P-Trap P-

SIZE · CODE	45	70	130
5/8" 10	•	•	
3/4" 12	•	•	
7/8" 14	•	•	
1-1/8" 18	•	•	
1-3/8" 22	•	•	
1-5/8" 26	•	•	
2-1/8" 34	•	•	

Return Bend C x Bend Rad. B-

SIZE · CODE	45	70	130
5/8 × 1-9/16 06-25		•	
5/8 × 2-1/4 06-36		•	
5/8 × 2-1/2 06-40		•	
1/2 × 1-1/2 08-24		•	
3/4 × 2-1/8 12-34		•	
7/8 × 2-1/2 14-40		•	
7/8 × 3-3/8 14-54		•	
1-1/8 × 3 18-48		•	
1-3/8 × 3-3/4 22-60		•	
1-5/8 × 4-1/2 26-72		•	
2-1/8 × 5-1/2 34-88		•	

Reducing Tee T-

SIZE · CODE	45	70	130
1/4 × 1/4 × 3/8 04-04-06		•	
5/16 × 5/16 × 1/4 05-05-04		•	
3/8 × 1/4 × 3/8 06-04-06		•	
3/8 × 3/8 × 1/4 06-06-04	•	•	
3/8 × 3/8 × 1/2 06-06-08	•	•	
3/8 × 3/8 × 5/8 06-06-10		•	
1/2 × 3/8 × 1/4 08-06-04		•	
1/2 × 3/8 × 3/8 08-06-06	•	•	•
1/2 × 3/8 × 1/2 08-06-08		•	
1/2 × 1/2 × 1/4 08-08-04	•	•	
1/2 × 1/2 × 3/8 08-08-06	•	•	•
1/2 × 1/2 × 5/8 08-08-10	•	•	
5/8 × 3/8 × 5/8 10-06-10	•	•	
5/8 × 1/2 × 3/8 10-08-06	•	•	
5/8 × 1/2 × 1/2 10-08-08	•	•	•
5/8 × 1/2 × 5/8 10-08-10		•	
5/8 × 5/8 × 1/4 10-10-04	•	•	
5/8 × 5/8 × 3/8 10-10-06	•	•	•
5/8 × 5/8 × 1/2 10-10-08	•	•	•
5/8 × 5/8 × 7/8 10-10-14	•	•	
3/4 × 3/4 × 3/8 12-12-06		•	
3/4 × 3/4 × 1/2 12-12-08	•	•	•
3/4 × 3/4 × 5/8 12-12-10			•
7/8 × 5/8 × 3/8 14-10-06	•	•	
7/8 × 5/8 × 1/2 14-10-08	•	•	
7/8 × 5/8 × 5/8 14-10-10	•	•	
7/8 × 5/8 × 7/8 14-10-14	•	•	
7/8 × 3/4 × 3/4 14-12-12	•	•	
7/8 × 7/8 × 3/8 14-14-06	•	•	
7/8 × 7/8 × 1/2 14-14-08	•	•	•
7/8 × 7/8 × 5/8 14-14-10	•	•	•
7/8 × 7/8 × 3/4 14-14-12			•
7/8 × 7/8 × 1-1/8 14-14-18	•	•	
1-1/8 × 5/8 × 1-1/8 18-10-18		•	
1-1/8 × 7/8 × 1/2 18-14-08			•
1-1/8 × 7/8 × 7/8 18-14-14	•	•	
1-1/8 × 7/8 × 1-1/8 18-14-18	•	•	
1-1/8 × 1-1/8 × 1/2 18-18-08		•	
1-1/8 × 1-1/8 × 5/8 18-18-10	•	•	
1-1/8 × 1-1/8 × 3/4 18-18-12	•	•	•
1-1/8 × 1-1/8 × 7/8 18-18-14	•	•	•
1-1/8 × 1-1/8 × 1-3/8 18-18-22		•	
1-1/8 × 1-1/8 × 1-5/8 18-18-26		•	
1-3/8 × 7/8 × 7/8 22-14-14		•	
1-3/8 × 7/8 × 1-1/8 22-14-18		•	
1-3/8 × 7/8 × 1-3/8 22-14-22		•	
1-3/8 × 1-1/8 × 5/8 22-18-10		•	
1-3/8 × 1-1/8 × 7/8 22-18-14		•	
1-3/8 × 1-1/8 × 1-1/8 22-18-18		•	
1-3/8 × 1-1/8 × 1-3/8 22-18-22		•	
1-3/8 × 1-3/8 × 1/2 22-22-08		•	
1-3/8 × 1-3/8 × 5/8 22-22-10		•	
1-3/8 × 1-3/8 × 3/4 22-22-12			•
1-3/8 × 1-3/8 × 7/8 22-22-14	•	•	•
1-3/8 × 1-3/8 × 1-1/8 22-22-18	•	•	•

Reducing Tee (cont.) T-

SIZE · CODE	45	70	130
1-3/8 × 1-3/8 × 1-5/8 22-22-26		•	
1-5/8 × 7/8 × 1-5/8 26-14-26		•	
1-5/8 × 1-1/8 × 7/8 26-18-14		•	
1-5/8 × 1-1/8 × 1-1/8 26-18-18		•	
1-5/8 × 1-1/8 × 1-5/8 26-18-26		•	
1-5/8 × 1-3/8 × 7/8 26-22-14		•	
1-5/8 × 1-3/8 × 1-1/8 26-22-18		•	
1-5/8 × 1-3/8 × 1-3/8 26-22-22		•	
1-5/8 × 1-3/8 × 1-5/8 26-22-26		•	
1-5/8 × 1-5/8 × 1/2 26-26-08		•	
1-5/8 × 1-5/8 × 5/8 26-26-10		•	
1-5/8 × 1-5/8 × 3/4 26-26-12			•
1-5/8 × 1-5/8 × 7/8 26-26-14	•	•	•
1-5/8 × 1-5/8 × 1-1/8 26-26-18	•	•	•
1-5/8 × 1-5/8 × 1-3/8 26-26-22	•	•	•
1-5/8 × 1-5/8 × 2-1/8 26-26-34		•	
2-1/8 × 1-3/8 × 2-1/8 34-22-34		•	
2-1/8 × 1-5/8 × 1-5/8 34-26-26		•	
2-1/8 × 1-5/8 × 2-1/8 34-26-34		•	
2-1/8 × 2-1/8 × 1/2 34-34-08		•	
2-1/8 × 2-1/8 × 5/8 34-34-10		•	
2-1/8 × 2-1/8 × 7/8 34-34-14		•	
2-1/8 × 2-1/8 × 1-1/8 34-34-18	•	•	
2-1/8 × 2-1/8 × 1-3/8 34-34-22		•	
2-1/8 × 2-1/8 × 1-5/8 34-34-26	•	•	•
2-1/8 × 2-1/8 × 2-5/8 34-34-42		•	
2-1/8 × 2-1/8 × 3-1/8 34-34-50		•	
2-5/8 × 1-5/8 × 2-5/8 42-26-42		•	
2-5/8 × 2-1/8 × 2-1/8 42-34-34		•	
2-5/8 × 2-5/8 × 5/8 42-42-10		•	
2-5/8 × 2-5/8 × 1-1/8 42-42-18		•	
2-5/8 × 2-5/8 × 1-3/8 42-42-22		•	
2-5/8 × 2-5/8 × 1-5/8 42-42-26		•	
2-5/8 × 2-5/8 × 2-1/8 42-42-34		•	
3-1/8 × 3-1/8 × 1-1/8 50-50-18		•	
3-1/8 × 3-1/8 × 1-3/8 50-50-22		•	
3-1/8 × 3-1/8 × 1-5/8 50-50-26		•	
3-1/8 × 3-1/8 × 2-1/8 50-50-34	•	•	
3-1/8 × 3-1/8 × 2-5/8 50-50-42		•	
4-1/8 × 4-1/8 × 2-1/8 66-66-34	•	•	
4-1/8 × 4-1/8 × 3-1/8 66-66-50	•		

Tee **T-**

SIZE · CODE	45	70	130
3/16" 03		•	
1/4" 04	•	•	
5/16" 05		•	
3/8" 06	•	•	•
1/2" 08	•	•	•
5/8" 10	•	•	•
3/4" 12	•	•	•
7/8" 14	•	•	•
1" 16	•	•	
1-1/8" 18	•	•	•
1-3/8" 22	•	•	•
1-5/8" 26	•	•	•
2-1/8" 34	•	•	•
2-5/8" 42	•	•	•
3-1/8" 50		•	
3-5/8" 58		•	
4-1/8" 66		•	

Service Valve Tee **ST-**

SIZE · CODE	45	70	130
3/8 × 3/8 × 10 mm 06-06-10mm			•
1/2 × 1/2 × 10 mm 08-08-10mm			•
5/8 × 5/8 × 10 mm 10-10-10mm			•
3/4 × 3/4 × 10 mm 12-12-10mm			•
7/8 × 7/8 × 10 mm 14-14-10mm			•
1-1/8 × 1-1/8 × 10 mm 18-18-10mm			•
1-3/8 × 1-3/8 × 10 mm 22-22-10mm			•
1-5/8 × 1-5/8 × 10 mm 26-26-10mm			•
2-1/8 × 2-1/8 × 10 mm 34-34-10mm			•

2-Hole Tubing Strap **S-**

SIZE · CODE	45	70	130
1/4" 04		•	
3/8" 06		•	
1/2" 08	•	•	
5/8" 10	•	•	
3/4" 12		•	
7/8" 14	•	•	
1-1/8" 18	•	•	
1-3/8" 22	•	•	
1-5/8" 26	•	•	
2-1/8" 34		•	

Union **33-**

SIZE · CODE	45	70	130
3/8" 06		•	
1/2" 08	•	•	
5/8" 10	•	•	
7/8" 14	•	•	
1-1/8" 18	•	•	
1-3/8" 22		•	
1-5/8" 26		•	
2-1/8" 34		•	

GET IN TOUCH



Great product. Great service.

Based in Brisbane, Aker Advantage manufactures and distributes premium copper components for the HVACR industry, supplying wholesalers and OEMs across Australia. We focus on efficient service, responsive communication and on-time delivery.

PHONE

1800 312 412

EMAIL

sales@akeradvantage.com.au

WEBSITE

akeradvantage.com.au

HEAD OFFICE

**U9 358 Nudgee Road
Hendra QLD 4011**